



All dimensions are in mm; tolerances according to ISO 2768 m-H

**Interface**

According to

QLF® (Quick Lock Formula)

Rosenberger is an authorized QLF® manufacturer

**Documents**

N/A

**Material and plating**

**Connector parts**

- Center conductor
- Outer conductor
- Dielectric
- Substrate

**Material**

- Beryllium copper
- Brass
- PTFE
- Al<sub>2</sub>O<sub>3</sub>

**Plating**

- Gold, min. 1.27 µm, over nickel
- White bronze(e.g. Optalloy®)

**Technical Data Sheet****Rosenberger**

QMA

Termination  
Jack 1 Watt**28K1ER-001N3****Electrical data**

Impedance 50  $\Omega$   
 Frequency DC to 12.4 GHz  
 Return loss  $\geq 29$  dB, DC to 1 GHz  
 $\geq 21$  dB, 1 GHz to 2.5 GHz  
 $\geq 17$  dB, 2.5 GHz to 12.4 GHz

Power handling (at 25 °C, sea level) 1 W at 2.5 GHz, derated linearity by 0.01 W/K

**Mechanical data**

Mating cycles  $\geq 100$   
 Engagement force 27 N (typ.)  
 Disengagement force 20 N (typ.)  
 Retention force for interface  $\geq 60$  N

**Environmental data**

Temperature range -40 °C to +85 °C  
 RoHS compliant

**Tooling**

N/A

**Suitable cables**

N/A

**Packing**

Standard 100 pcs in bag  
 Weight 1.8 g/pce

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
Kerstin Herzog	12.07.05	Markus Müller	22.05.18	c00	18-1027	Marion Striegler	22.05.18
Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.de					Tel. : +49 8684 18-0 Email : info@rosenberger.de		Page 2 / 2